



- 11 psi (22 in Hg vacuum)
- 3.3 GPM – 11.0 GPM (0.4—1.5 cfm)
- Self-priming
- Can run dry without damage
- Quiet-running 115 VAC motor with optional speeds from 30, 60, 72 or 100 RPM
- Durable, lightweight Acetal plastic pump body and flanges
- Accommodates 1/2" – 1-1/4" hose
- Available with wide variety of hose connections

### Specifications / Options

Body & Ports *	Acetal (POM) Copolymer / Gray
Clamp Ring	Aluminum Motor Mounting Plate
Valves *	Flapper, Duckbill, Umbrella
Diaphragm *	Buna-N, Buna-N Double Sided, Neoprene, Viton, EPDM, Silicone
Clevis/Button Assembly *	SS Washer + Aluminum Clevis
Motor Ambient Temp	Ambient Temp: 14°F ~ 104°F (-10°C ~ 40°C)
Motor Enclosure	Provides limited protection against ingress of dust and water spray.

\* in contact with fluid

### Available 115 VAC Motors & Performance

Pump Flow Rate <sup>4</sup> (GPM)	Motor Speed <sup>3</sup> (Name-plate RPM)	Full Load Torque (in-lbs.)	Input HP	Full Load Amps	Max Pressure (psi)	Max Lift <sup>5</sup> (ft)	Max Head (ft)
3.3	30	118	1/19	1.4	10	20	23
6.6	60	133	1/8	1.6	11	20	25
7.9	72	111	1/8	1.6	10	20	23
11.0	100	80	1/8	1.6	7	16	16

<sup>4</sup> at 0 lift, 0 head

<sup>5</sup> Check valve recommended for lifts above 12 ft.

### Performance




Flow Rate	per stroke: 0.44 Qt (0.42L)
Max Lift	20 ft (6.1 m) <sup>1,2</sup>
Max Head	25 ft (7.6 m) <sup>1</sup>
Max Pressure	11 psi (0.7 bar) <sup>1</sup>
Max Vacuum	22 in Hg (0.7 bar) <sup>1,3</sup>
Max Service Temp	212°F (100°C)

<sup>1</sup> depending on choice of motor and valves

<sup>2</sup> with a check valve

<sup>3</sup> higher vacuum available when valves are wet

### Valve Options

Flapper	Duckbill	Umbrella
		
General purpose liquid transfer	For dirty liquid and sewage	Clear liquids
	Good vacuum service	Best vacuum service
For vertical pump mounts, inlet must be below outlet	Mount pump in any position	Mount pump in any position



### Available Ports

	in	1/2	3/4	1	1-1/8	1-1/4
	cm	1.27	1.91	2.54	2.86	3.18
Hose (Smooth)			•	S	•	•
NPT Female (Tapped)		•	•			
NPT Male (Threaded)			•	•		
Male Garden Hose (Threaded)			•			
Barbed			•		•	
Female Garden Hose Adapter			•			

S Standard • Optional


**NOTE: This pump is not potable-water rated.**

Quiet-running, efficient 115 VAC motor available in a range of speeds and torques.



	in	cm
A	8-1/4	21.0
B	7-1/4	18.4
C	9-5/8	24.4
D	12-3/4	32.4
E	4-5/16	11.0
F	6	15.2
G	10-1/4	26.0
H	9-5/8	24.4
Mounting Holes	1/4	0.64
Bolt Circle Diam.	6-1/8	15.6
Weight	16.1 lb	7.3 kg

# Guzzler® 115 VAC Electric Pump GE-0401D



**Example: GE-0401D-011-48-5050-BP**

- Guzzler Electric Pump
- Model style #0401D: Acetal Body, Opposite Side Ports
- No Variable Speed control option
- Buna-N Flapper Valves
- Buna Diaphragm
- SS Washer & Aluminum Clevis
- Motor Mounting Plate Clamp Ring
- Inlet: 1" Smooth
- Outlet: 1" Smooth

Guzzler Product	
Option	Code
Electric Pump	GE

Style (Family)	
Option	Code
Acetal, Opp. Side Ports	0401D

Speed Control	
Option	Code
None	0

Valves	
Option	Code
Flapper (Buna-N)	1
Flapper (White Buna)	2
Flapper (Neoprene)	3
Flapper (Viton)	4
Flapper (EPDM)	5
Duckbill (Buna-N)	6
Umbrella (Silicone)	7

Diaphragm	
Option	Code
Buna Nitrile	1
Buna-N 3-Ply	2
Neoprene	3
Viton	4
EPDM	5
Silicone	7

**GE - 0401D - 0 1 1 - 4 8 - 50 50 - BP**

Clevis/Button Assembly	
Option	Code
SS Washer & Alum Clevis	4

Clamp Ring	
Option	Code
Motor Mounting Plate	8

Hose Connections		
Option	Code	
	Inlet	Outlet
1/2" NPT Tapped	31	31
3/4" Smooth	40	40
3/4" NPT Tapped	41	41
3/4" NPT Threaded	42	42
3/4" Barbed	43	43
3/4" Female GH Adapter	45	45
3/4" Male Garden Hose	46	46
1" Smooth	50	50
1" NPT Threaded	52	52
1-1/8" Smooth	60	60
1-1/8" Barbed	63	63
1-1/4" Smooth	70	70

115 VAC Motors		
Speed (rpm)	Torque (in-lbs)	Code
30	118	BD
60	133	BK
72	111	BP
100	80	BT

